

## Accessories

### VGM32-MS68 15-25 BG

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



With blueglobe®, Weidmüller has introduced a cable gland from Pflitsch into its portfolio that convinces both in terms of reliability and functionality.

A large sealing range from 1.5 to 77 mm thanks to removable inlets with just 11 cable glands, highly effective sealing, excellent strain relief and a groove-guided upstream O-ring – these are the features of the blueglobe® cable glands which Weidmüller offers in brass and stainless steel.

The heart of the blueglobe® cable gland is the spherical seal insert that squeezes the cable gently and over a large area. This permanently avoids the incisive notch effect that is common with lamella systems.

#### General ordering data

Type	VGM32-MS68 15-25 BG
Order No.	<a href="#">1193610000</a>
Version	Heavy Duty Connectors, Accessories, Cable gland, Brass, nickel-plated
GTIN (EAN)	4032248976621
Qty.	25 pc(s).

## Accessories

### VGM32-MS68 15-25 BG

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Length	40 mm	Length (inches)	1.575 inch
Net weight	112.88 g		

### Temperatures

Limit temperature	-40 °C ... 130 °C
-------------------	-------------------

### General data

AF size	36 mm	Cable diameter, max.	25 mm
Cable diameter, min.	15 mm	Cable gland	M 32
External thread	M 32	Length of thread	8 mm
Material	Brass, nickel-plated	O-Ring	NBR
Protection degree	IP68	Sealing material	TPE
Tightening torque, max.	15 Nm	Type of sealing	Rubber ring

### Classifications

ETIM 5.0	EC002625	ETIM 6.0	EC000441
eClass 6.2	27-18-92-34	eClass 7.1	27-18-92-34
eClass 8.1	27-18-92-34	eClass 9.0	27-18-92-34
eClass 9.1	27-14-44-32		

### Product information

Descriptive text ordering data	When using mounting covers with 3 X M 40 cable input threads, the elongated version must be used for the cable gland in the middle.
--------------------------------	---

### Approvals

Approvals



ROHS	Conform
------	---------

### Downloads

Brochure/Catalogue	<a href="#">CAT 3 HDC 17/18 EN</a> <a href="#">CAT 5 ENCL 17/18 EN</a> <a href="#">FL FIELDWIRING EN</a>
Engineering Data	<a href="#">EPLAN</a>